



coatmaster

measure up. contactless.

coatmaster Inline

Non-contact coating thickness measurement for continuous industrial use



PATENTED
TECHNOLOGY



Avoid rework and rejects.

Detect and correct deviations early in the process.



Save material.

Reduce your material consumption by up to 30%. This saves money and protects the environment.



Document continuously.

Document your coating process for you and your customers.

Technical data

Substrate: Metal

Powder coatings before curing	10 – 300 µm
Wet coatings before drying	1 – 300 µm
Cured powder coatings	1 – 2000 µm
Dried wet coatings	1 – 2000 µm

Substrate: Plastic/Rubber

Wet coatings before drying	5 – 150 µm
Dried wet coatings	5 – 50 µm

Substrate: Wood/MDF

Powder coatings before curing	10 – 150 µm
Wet coatings before drying	10 – 250 µm

Measuring time	from 20 ms
Distance tolerance	5 – 120 cm
Tilt tolerance	± 70°
Measurement on moving and jiggling parts	yes up to 120 m/min
Relative standard deviation*	<1 %
Smallest measuring point	1 mm
Works on all colors (incl. white)	yes
Real-time data access via ERP and Internet browser	yes
Dimensions measuring head HxWxD	160 x 205 x 210 mm
Weight measuring head	5.2 kg

All information applies to a typical coating system and substrate.

The exact limits always depend on the physical properties of the coating material.

Even if the parameters are within the specified ranges, certain combinations may not be achievable.

For an accurate assessment, please contact coatmaster AG.

Actual performance may vary, and specifications are subject to change without prior notice.

*60 µm powder coating before curing on aluminium, 5 cm working distance.

coatmaster AG

Flugplatzstrasse 5

CH-8404 Winterthur

Tel +41 52 212 02 77

info@coatmaster.com

www.coatmaster.com



Learn more

All information about
thickness measurement
with coatmaster